



GOEDICKE
WERKZEUGMASCHINEN



Goedicke Werkzeugmaschinenhandels GmbH

Heinz-Nixdorf-Str. 2
D-74172 Neckarsulm
+49-(0)7132-999 360

info@goedicke.com
www.goedicke.com

Drawing Press -hydraulic-

Stock number **7-27919**
Make **AP&T**
Model **ZF-12500-46/25 MB**

Control **PLC SIEMENS S7**

Year of **2000**

Condition **★★★★★★★★★**



Press Design

frame design

H-frame

Press forces

total force (nominal)

1250 to

Press Table

clamping surface (left-right)

4600 mm

clamping surface (front-back)

2500 mm

force of cushion

400 to

moving bolster

yes

Ram

ram force

1250 to

clamping surface (left-right)

4600 mm

clamping surface (front-back)

2500 mm

stroke

1700 mm

restoring force of ram

95 to

force of cushion

300 to

ram ejectors

yes

Tool Assembly Dimensions

daylight max.

2300 mm

distance between columns (H-frame)

4600 mm

Free passage between side columns (width)

1600 mm

Die Cushion (table cushion)

force of cushion

400 to

stroke

400 mm

clamping surface (left-right)

3850 mm

clamping surface (front-back)

2200 mm



working principle

hydraulic

Die Cushion (table cushion)

force of cushion

300 to

stroke

200 mm

clamping surface (left-right)

3700 mm

clamping surface (front-back)

1900 mm

working principle

hydraulic

Electrical specifications

total power consumption

473 kW

Dimensions / weights

total weight approx.

285000 kg

Attachments for Presses

light barrier

yes

acc. to actual accident protection regulation

yes

hydraulic overload protection

yes

Technical description

- Cushion in table with 400 ton and 400 mm stroke.
- Cushion in ram with 300 to. and 200 mm stroke.
- Stroke shock absorber 4 x 150 ton and 20 mm stroke.
- Adjustment of shock absorbers max. 600 mm.
- Max. speed of ram (down). = 390 mm/ sec.
- Max. press-speed = 48 mm/sec.
- Max. working-speed = 32 mm/sec.- 200 mm/sec.
- Max. speed of ram (up). = 340 mm/sec.



Data / Pictures

Get technical data and pictures via WhatsApp now!



Data / Pictures

Get technical data and pictures via WhatsApp now!

